

WOOD DECK CAR HAULER TRAILERS - 5" CHANNEL - MODEL AW

PROFESSIONAL GRADE

- Treated wood deck
- Standard 2 ft. dovetail
- 82" between fenders
- Double eye spring suspension
- 5' self-storing punched surface ramps
- 2 5/16 A frame coupler
- Swing-up jack
- Tear drop fenders with backs
- Steps Front And Rear of Fenders
- Stake pockets with rub-rail
- Self-charging break away kit, safety chains, and Full DOT reflective tape
- All rubber mounted sealed beam LED lighting with U.S. made sealed modular harness with 5 year warranty
- Primed, 2 coats of automotive grade acrylic enamel, pin striped



GVWR – 7,000 lb.

- 3,500 lb. braking axles with 4 wheel brakes
- ST205/75R15 load range "D" 8 ply rating Premium West Lake Radial tires
- 5" channel frame
- 3" channel cross members. 24" spacing
- 4" channel wrap around tongue

GVWR – 8,000 lb.

- 4,000 lb. braking axles with 4 wheel brakes
- ST225/75R15 load range "E" 10 ply rating Premium West Lake Radial tires
- 5" channel frame
- 3" channel cross members. 24" spacing
- 4" channel wrap around tongue

GVWR – 10,000 lb.

- 5,200 lb. braking axles with 4 wheel brakes
- ST225/75R15 load range "E" 10 ply rating Premium West Lake Radial tires
- 5" channel frame
- 3" channel cross members. 16" spacing
- 5" channel wrap around tongue

GENERAL DUTY

- Treated wood deck
- Standard 2 ft. dovetail
- 82" between fenders
- Double eye spring suspension
- 5' self-storing ladder style ramps
- 2 5/16 A frame coupler
- Swing-up jack
- Tear drop fenders with backs
- Steps Front And Rear of Fenders
- Stake pockets, self-charging break away kit, safety chains, and skip reflective tape
- All rubber mounted sealed beam lighting, with conventional wiring and gel-filled connectors.
- Primed, 2 coats of automotive grade acrylic enamel, pin striped



GVWR – 7,000 lb.

- 3,500 lb. braking axles with 4 wheel brakes
- ST205/75R15 LRC 6 ply rating Castle Rock Radial tires
- 5" channel frame
- 3" channel cross members. 24" spacing
- 4" channel wrap around tongue

GVWR – 8,000 lb.

- 4,000 lb. braking axles with 4 wheel brakes
- ST225/75R15 LRD 8 ply rating Castle Rock Radial tires
- 5" channel frame
- 3" channel cross members. 24" spacing
- 4" channel wrap around tongue

GVWR – 10,000 lb.

- 5,200 lb. braking axles with 4 wheel brakes
- ST225/75R15 LRD 8 ply rating Castle Rock Radial tires
- 5" channel frame
- 3" channel cross members. 24" spacing
- 5" channel wrap around tongue