

FENDER EQUIPMENT TRAILERS – 6" CHANNEL - MODEL DH

PROFESSIONAL GRADE

- Treated wood deck
- 82" between fenders
- 6" channel frame • 3" channel cross members. 16" spacing
- 5' swing up ramps with support foot
- HD 4" Channel Ramps With Spring Assist on 15,000 GVWR
- 2 5/16 adjustable coupler (HD Cast Iron on 15,000 GVWR)
- 12,000 lb. drop-foot jack
- Heavy duty diamond plate fenders with backs
- Tool tray with lockable lid
- Stake pockets and rubrail
- Self-charging break away kit, safety chains and full DOT reflective tape.
- All rubber mounted LED sealed beam lighting with U.S. made sealed modular harness with 5 year warranty
- Primed, 2 coats of automotive grade acrylic enamel, pin striped

10,000 GVWR

- 5,200 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST225/75R15 load range "E" 10 ply rating Premium West Lake Radial tires
- 5" channel wrap around tongue with toolbox and lockable lid

12,000 GVWR

- 6,000 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST235/80R16 load range "E" 10 ply rating Premium West Lake Radial tires
- 6" channel wrap around tongue with toolbox and lockable lid

15,000 GVWR

- 7,000 lb. braking axles with 4 wheel brakes
- Slipper spring suspension
- ST235/80R16 load range "E" 10 ply rating Premium West Lake Radial tires
- 6" channel wrap around tongue with toolbox and lockable lid



OPTIONS

- Cleated Dovetail • Spring assist on ramps
- Heavy duty split gate with spring assist
- Third ramp
- Diamond plate deck (standard length)
- Spare tire and wheel • Spare Mount
- Upgrade to all steel belted load range "G" tires
- Load range "G" spare tire

AVAILABLE SIZES 16' • 18' • 20'

SIZE	PRICE

GENERAL DUTY

- Treated wood deck
- 82" between fenders
- 6" channel frame • 3" channel cross members. 24" spacing
- 5' swing up ramps with support foot
- 2 5/16 adjustable coupler • 7,000 lb. drop-foot jack
- Heavy duty diamond plate fenders with backs
- Stake pockets
- Self-charging break away kit, safety chains, DOT reflective tape, and all rubber mounted sealed beam lighting with conventional wiring with gel filled connectors.
- Primed, 2 coats of automotive grade acrylic enamel, pin striped

10,000 GVWR

- 5,200 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST225/75R15 LRD 8 ply rating Castle Rock Radial tires
- 5" channel wrap around tongue

12,000 GVWR

- 6,000 lb. braking axles with 4 wheel brakes
- Double eye spring suspension
- ST235/80R16 LRE 10 ply rating Castle Rock Radial tires
- 6" channel wrap around tongue

14,000 GVWR

- 7,000 lb. braking axles with 4 wheel brakes
- Slipper spring suspension
- ST235/80R16 LRE 10 ply rating Castle Rock Radial tires
- 6" channel wrap around tongue



GENERAL DUTY OPTIONS

- LED lighting
- Toolbox and lockable lid
- 12,000 lb. drop foot jack
- Cleated Dovetail • Spring assist on ramps
- Heavy duty split gate with spring assist
- Third ramp
- Diamond plate deck (standard length)
- Spare tire and wheel • Spare Mount

AVAILABLE SIZES 16' • 18' • 20'

SIZE	PRICE