



Standard Features

- 7" channel mainframe
- 6" channel side frame
- 3" channel cross members on 24" centers
- Dexter Torflex torsion axles
- Electric brakes (all-axle)
- Rubber-mounted LED lighting
- Treated and kiln dried pine decking
- Tread plate over wheel wells for lower deck height
- 5' ladder ramps with double hinge; ramps able to stand up or lay flat on tail
- 4' dovetail
- PPG epoxy primer and urethane paint

Available Colors: ■ ■ ■



Top left: Standard stand up ramps **Top right:** Plated wheel well for lower profile
Bottom left: Optional full/split gates **Bottom right:** Optional front tool box

Model	GAWR	GVWR	Curb Wt.*	Payload**	Length	Width	Axle Type	Frame Size	CM Centers
16+4 C-series	5,000	9,990	3,680 lbs	7,320 lbs	16'+4'	102"	Torsion	7" channel	24"
18+4 C-series	5,000	9,990	4,000 lbs	7,000 lbs	18'+4'	102"	Torsion	7" channel	24"
20+4 C-series	5,000	9,990	4,380 lbs	6,620 lbs	20'+4'	102"	Torsion	7" channel	24"

* Curb weight is based on a base model unit with no options.

** Payload is calculated on 10% transfer weight on bumper hitch when weight is distributed evenly.

Optional Features

- Full/split gates
- 6K or 7K axles
- Lockable tool box
- No dovetail
- Channel gooseneck
- Extra D-rings
- Spare tire/wheel
- Blackwood (full trailer, tread space or dovetail)