



HTH model with full power tilt shown



Top: 17.5" H-rated tires Bottom: Standard tool box and adjustable coupler

Standard Features (HT, HTH)

- Bulldog 10,000 lb. jack (4" square)
- 2 5/16" heavy duty coupler
- Dexter Torflex torsion axles
- Quality radial tires
- Electric brakes (all-axle)
- Rubber-mounted LED lighting
- 11-gauge diamond plate fenders
- Lockable tool box
- Treated and kiln dried pine decking
- Hydraulic dampening cylinder (HT model)
- Hydraulic power cylinder (HTH model)
- Bead blasted before painting
- PPG epoxy primer and urethane paint

Model	GAWR	GVWR	Curb Wt.*	Payload**	Length	Width (between fenders)	Axle Type	Frame Size	CM Centers
UT-21 HT	6,000	12,000	3,680 lbs	9,520 lbs	4' stat.+17' tilt	81"	Torsion	6" channel	24"
UT-23 HT	6,000	12,000	3,790 lbs	9,410 lbs	4' stat.+19' tilt	81"	Torsion	6" channel	24"
UT-21 HTH	6,000	12,000	3,070 lbs	10,130 lbs	21' full tilt	81"	Torsion	6" channel	24"
UT-23 HTH	6,000	12,000	3,270 lbs	9,880 lbs	23' full tilt	81"	Torsion	6" channel	24"

* Curb weight is based on a base model unit with no options.

** Payload is calculated on 10% transfer weight on bumper hitch when weight is distributed evenly.

Optional Features (HT, HTH)

- 7K axles (adds 280 lbs. to curb weight)
- 8K axles - includes 8" main frame, cross members on 16" centers and 17.5" H-rated tires
- Spare tire/wheel
- Pintle ring in lieu of 2 5/16" coupler
- Gooseneck
- Wireless remote control (HTH models)
- Blackwood lumber



UT-12 SAT model shown (5K axle standard and 6k axle optional)

Model	GAWR	GVWR	Curb Wt.*	Payload**	Length	Width (between fenders)	Axle Type	Frame Size	CM Centers
UT-12 SAT	5,000	5,000	1,640 lbs	3,860 lbs	1' full tilt	81"	Torsion	3" x 5" x 1/4"	24"

* Curb weight is based on a base model unit with no options.

** Payload is calculated on 10% transfer weight on bumper hitch when weight is distributed evenly.

Available Colors: ■ ■ ■