



Standard Features on all Livestock Trailers – Bumper and Gooseneck Models

- 3" x 5" x 1/4" structural angle main frame
- 3" x 2" x 3/16" cross members
- S-model 24" centers
- H-model 16" centers
- 4" channel tongue
- 14-gauge sides and fenders
- 16-gauge roof

- 6" roof radius
- 3" x 4" tube at rear corners
- 12-volt breakaway with battery
- Bulldog coupler and jack
- Dexter Torflex torsion axles
- Electric brakes (all-axle)
- Quality radial tires

- Rubber-mounted LED lighting
- Double tail lights
- Treated and kiln dried pine flooring
- PPG epoxy primer and urethane
- Aluminum tread plate on front round and front of fenders

Model	GAWR	GVWR	Curb. Wt.*	Payload**	Floor Length	Floor Width	Intr. Height	Ctr. Gate
SB-12 6S	3,500	7,000	2,520 lbs	5,180 lbs	12'	6'	6'6"	0
SB-14 6S	3,500	7,000	2,960 lbs	4,740 lbs	14'	6'	6'6"	1
SB-16 6S	3,500	7,000	3,120 lbs	4,580 lbs	16'	6'	6'6"	1
SB-18 6S	3,500	7,000	3,455 lbs	4,245 lbs	18'	6'	6'6"	1
SB-12 7S	3,500	7,000	3,090 lbs	4,610 lbs	12'	6'8"	6'6"	0
SB-14 7S	3,500	7,000	3,140 lbs	4,560 lbs	14'	6'8"	6'6"	1
SB-16 7S	3,500	7,000	3,200 lbs	4,500 lbs	16'	6'8"	6'6"	1
SB-187S	6,000	12,000	3,850 lbs	9,350 lbs	18'	6'8"	6'6"	1
SB-20 7S	6,000	12,000	3,990 lbs	9,210 lbs	20'	6'8"	6'6"	1
SB-14 6H	6,000	12,000	3,410 lbs	9,790 lbs	14'	6'	6'6"	1
SB-16 6H	6,000	12,000	3,630 lbs	9,570 lbs	16'	6'	6'6"	1
SB-147H	6,000	12,000	3,585 lbs	9,615 lbs	14'	6'8"	6'6"	1
SB-16 7H	6,000	12,000	3,700 lbs	9,500 lbs	16'	6'8"	6'6"	1
SB-18 7H	6,000	12,000	4,245 lbs	8,955 lbs	18'	6'8"	6'6"	1

^{*} Curb weight is based on a base model unit with no options.

Optional Features – Bumper Models

- 5K axles
- 5' tall
- 7' tall
- Smooth skin
- Low sides
- Extra center gate
- Sliding center gate
- Plexiglass front window
- Back up lights
- Rubber bumper
- Spare tire/wheel
- Blackwood lumber[™]



5' tall option

Low sides

^{**} Payload is calculated on 10% transfer weight on bumper hitch when weight is distributed evenly.